



PIACENTINA SOFT

Piacentina Soft Blanco ABS

PRICE / M2 (VAT INCLUDED)

CHARACTERISTICS

Finish: Natural

Boxes / Pallet: 40

Kg / Box: 24.26

Kg / Pallet: 970

Degree of detonation: V3 (Medium)

Pieces / Box: 3

M2 / Box: 1.13

M2 / Pallet: 45.2



Installation

Installation: Pavement



Critical angle of slip in wet areas when walking barefoot (DIN 51097 - Ramp)

Critical angle of slip in wet areas when walking barefoot (DIN 51097 - Ramp):

Glazed Porcelain



mm

Glazed Porcelain

Suitable for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens.



Destonified



Critical angle of slip (DIN 51130 - Ramp)

Critical sliding angle (DIN 51130 - Ramp): R-11



Slip resistance (CTE ENV 12633 - Pendulum)

Slip resistance (CTE ENV 12633 - Pendulum): Class 3



Recycling

Recycled:

## Piacentina Soft

Industrial inspiration. With roughness as a defining trait, the traditional Piacentina stone is the inspiration of this glazed porcelain, highly resistant and versatile. The diverse lines within this Piacentina range make it the perfect candidate for professional or domestic projects. The rectified high-end range in 100x50 R cm., the medium range in 51x102 cm., not rectified and 61.5x61.5 cm. and the entry level with floor tiles in 31x61 cm. Available in Blanco, Gris and Arena and range available in 50x100 R cm, 61.5x61.5 cm and 31x61 cm.



### MANUALS AND RESOURCES



PDF

[Product technical certificate](#)

#technology\_text

**Glazed Porcelain****Glazed Porcelain**

Suitable for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens.