Roca



CHARACTERISTICS

Finish: Natural Boxes / Pallet: 22 Kg / Box: 10.09 Kg / Pallet: 221.89 Degree of detonation: V3 (Medium) Pieces / Box: 2 M2 / Box: 0.38 M2 / Pallet: 8.36



Installation Installation: Pavement



Colored Porcelain Highly resistant tiles for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens. •

mm

20 M M

Piamonte Gris

PRICE / M2 (VAT INCLUDED)



Critical angle of slip (DIN 51130 -Ramp) Critical sliding angle (DIN 51130 - Ramp): R-11



Slip resistance (CTE ENV 12633 -Pendulum) Slip resistance (CTE ENV 12633 -Pendulum): Class 3

20mm

The compact for the long-haul. The new Roca 20mm hickened pavements surpass the high performance, functionality and aesthetics of natural materials used in flooring. The extraordinary features of this stoneware challenge stone in the use as a pavement installed in exteriors and in high transit areas. In these collections the pavement has gained consistency and thickness to increase its resistance. Along with this, the Roca technology adds qualities such as the minimum porosity of the parts, long-lasting colours with the passage of time, certified Class 3 CTE anti-slip properties and its adaptation in diverse spaces.

MANUALS AND RESOURCES

Product technical certificate



#technology_text

White Body

Colored Porcelain

Highly resistant tiles for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens.